



TECHNICAL DATA SHEET

1600-O-005

1600 DESIGNER SERIES HYBRID SOCKET OUTLETS



Description

This socket outlet is designed for ease of installation and having all the advantages and design features. These products can be quickly installed as replacements for existing switch plate or in new installations.

Features

- Use of high impact resistant material, flame retarding & UV stabilized polycarbonate
- Socket mechanism constructed in compact & simple manner with minimum parts
- Large terminal faces to provide maximum installer versatility even in confined spaces
- Base plate is well designed to withstand any force applied by insertion of plugs or the operation of switches
- Clip on covers conceal mounting screws, simplify finishing & decorating
- Cover plate comes in metal & polycarbonate with quality gloss finish

Main Application

Suitable for switching to loads at areas such as living room, bedroom & kitchen. Commercial areas such as shopping complex, restaurants, cafeterias, hotel & etc.

Materials & Finish

- Use of polycarbonate for all plastic components
- Brass & Copper for all conductivity components
- All contact point is silver welded for best performance

Option

Accessories and color options upon request

Quantity

Box Quantity : 10 pcs
Outer Box : 100 pcs

TECHNICAL SPECIFICATION

Electrical

Voltage rating: 250V a.c.

Unit	Rating	Terminal capacity
10A sockets	10A	2 x 1.5mm ²
16A sockets	16A	2 x 1.5mm ²

Physical



Ambient operating temperature: -5°C to +40°C

Max. installation altitude: 2000 meters

Dimension

	L	X	W	X	H	
Plate Size	:	89	x	89	x	12.5mm
Mounting Centres	:	60.3mm				

WIRING DIAGRAM



1679 1 Gang Hybrid Socket

PRODUCT RANGE

Unswitched Socket Outlets

Description

1 Gang Hybrid Socket Outlet

CAT No.

1679