



TECHNICAL DATA SHEET

DECOR-S-001

DÉCOR SERIES 10Amp DECOR SWITCHES



TECHNICAL SPECIFICATION

Electrical

Voltage rating: 250V a.c.

Unit	Rating	Terminal capacity
10A switches	10AX	4 x 1.5mm ²

Physical

Ambient operating temperature: -5°C to +40°C
Max. installation altitude: 2000 meters

Dimension

	L X W X H
1 Gang Plate Size :	89 x 89 x 6.7mm
Mounting Centres :	60.3mm

PRODUCT RANGE

Decor Switches with 10AX Modules

Description

- 1 Gang 1 Way Single Pole (SP)
- 1 Gang 2 Way SP
- 1 Gang 1 Way SP with Neon
- 1 Gang 2 Way SP with Neon
- 1 Gang 1 Way Spring Return SP
- 1 Gang 2 Way Spring Return SP
- 2 Gang 1 Way SP
- 2 Gang 2 Way SP
- 2 Gang 1 Way SP with Neon
- 2 Gang 2 Way SP with Neon
- 3 Gang 1 Way SP
- 3 Gang 2 Way SP
- 3 Gang 1 Way SP with Neon
- 3 Gang 2 Way SP with Neon
- 1 Gang Intermediate Module

CAT No.

- 1681L/1W
- 1681L/2W
- 1681LN/1W
- 1681LN/2W
- 1681/1W BELL
- 1681/2W BELL
- 1682L/1W
- 1682L/2W
- 1682LN/1W
- 1682LN/2W
- 1683L/1W
- 1683L/2W
- 1683LN/1W
- 1683LN/2W
- 1685L

Description

The Decor switches are a new range of large rocker switches which complements the highly successful 1600 Series. This new generation of switches is designed with features which enhance the interior settings with blend of elegance.

Features

- Breakthrough in style with quality plate finishes of pleasant looks
- Use of high impact resistant material, flame retarding & UV stabilized polycarbonate
- Switch mechanism constructed in compact & simple manner with minimum parts
- Slim front plates with 7mm
- Removable convenience & concealed screws
- Interchangeable cover plates that comes with various selection of decoration colors with an elegant, gloss finish that is easy to clean

Main Application

Suitable for switching fluorescent or inductive loads at areas such as living room, bedroom & kitchen Commercial areas such as shopping complex, restaurants, cafeterias, hotel & etc

Materials & Finish

- Use of polycarbonate for all plastic components
- Brass & Copper for all conductivity components
- All contact point is silver welded for best performance

Option

Accessories and color options upon request


Standards & Approvals

Switches comply:
BSEN / IEC 60669-1


Quantity

Box Quantity : 10 pcs
Outer Box : 100 pcs


WIRING DIAGRAM




1681L/1W Single Pole 1 Gang 1 Way Switch
(Same application for 1682L/1W & 1683L/1W)




1681L/1W BELL Single Pole 1 Gang 1 Way BELL Switch (1 Way Spring Return Switching to Load)




1681LN/1W Single Pole 1 Gang 1 Way Switch
(Same application for 1682LN/1W & 1683LN/1W)




1681L/2W Single Pole 1 Gang 2 Way Switch
(Same application for 1682L/2W & 1683L/2W)




1681LN/2W Single Pole 1 Gang 2 Way Switch
(Same application for 1682LN/2W & 1683LN/2W)



1681L/2W Single Pole 1 Gang 2 Way Switch
(Same application for 1682L/2W & 1683L/2W)



1681L/2W Single Pole 1 Gang 2 Way Switch
(Same application for 1682L/2W & 1683L/2W)



1685L Single Pole 10AX Intermediate Switch